



DN		100	125	150	200	250	300	350	400
Ø d		114,3	139,7	168,3	219,1	273	323,9	355,6	406,4
Ø D		168,3	219,1	273	323,9	355,6	406,4	508	609,6
h	PN 10	182	217	249	292	325	363	423	478
	PN 16	182	217	249	292	327	373	437	491
	PN 25	195	230	269	310	345	387	455	516
	PN 40	195	230	269	318	362	410	480	541
b	PN 10	335	385	449	519	677	728	957	1012
	PN 16	335	385	449	519	679	738	971	1025
	PN 25	348	398	469	537	697	752	989	1050
	PN 40	348	398	469	545	714	775	1014	1075
l	PN 10	533	625	735	841	1026	1105	1413	1522
	PN 16	533	625	735	851	1024	1128	1442	1550
	PN 25	566	656	773	883	1078	1167	1495	1605
	PN 40	566	664	790	914	1120	1215	1535	/
A		450	550	670	780	970	1050	1350	1450
Gewicht kg	PN 10	47	72	111	154	213	270	465	634
	PN 16	47	72	116	164	231	308	530	754
	PN 25	61	90	144	204	292	421	646	916
	PN 40	66	109	171	267	389	580	723	0

Lochbleche (DIN 24041)

Rundlochung	Ø w (mm)	3,1	4,0	5,0	6,0
Teilung	t (mm)	4,5	6,0	8,0	8,0
Lochblechdicke	s (mm)	gestanzte 1,0 bis 3,0 mm dick			
freie Siebfläche	(%)	43,1	40,0	35,4	51,0

Drahtgewebe (DIN ISO 4783-2)

lichte Maschenweite	w (mm)	0,1	0,25	0,5	1,0	1,5	2,0
Drahtdurchmesser	Ø d (mm)	0,063	0,1	0,2	0,5	0,5	0,9
freie Siebfläche	(%)	38,0	51,0	51,0	44,0	56,0	48,0