



DN		100	125	150	200	250	300	350	400
Ø d		114,3	139,7	168,3	219,1	273	323,9	355,6	406,4
Ø D		168,3	219,1	273	323,9	355,6	406,4	508	609,6
h		130	162	194	230	257	295	355	355
b		283	330	394	457	610	660	889	939
l	PN 10	481	570	680	779	958	1037	1345	1450
	PN 16	481	570	680	789	972	1050	1360	1465
	PN 25	501	588	698	803	990	1075	1395	1495
	PN 40	501	596	715	826	1015	1100	1410	/
A		450	550	670	780	970	1050	1350	1450
Gewicht kg	PN 10	38	59	95	131	183	235	417	577
	PN 16	38	59	100	142	200	264	468	674
	PN 25	47	72	120	170	243	359	551	792
	PN 40	52	91	147	224	319	480	587	0

Lochbleche (DIN 24041)						
Rundlochung	Ø w (mm)		3,1	4,0	5,0	6,0
Teilung	t (mm)		4,5	6,0	8,0	8,0
Lochblechdicke	s (mm)	gestanzt 1,0 bis 3,0 mm dick				
freie Siebfläche	(%)		43,1	40,0	35,4	51,0

Drahtgewebe (DIN ISO 4783-2)								
lichte Maschenweite	w (mm)		0,1	0,25	0,5	1,0	1,5	2,0
Drahtdurchmesser	Ø d (mm)		0,063	0,1	0,2	0,5	0,5	0,9
freie Siebfläche	(%)		38,0	51,0	51,0	44,0	56,0	48,0